

TRANSMITTAL OF INFORMATION DISCLOSURE STATEMENT

(Under 37 CFR 1.97(b) or 1.97(c))

Docket No.
DE3-0089/DP-300793

In Re Application Of: THADDEUS SCHRODER ET AL

JAN 15 2002

PATENT & TRADEMARK OFFICE

Serial No.
09/663,030Filing Date
September 15, 2000Examiner
D. DePumpoGroup Art Unit
3611**RECEIVED**

JAN 24 2002

GROUP 3600

Title: PIEZORESISTIVE TORQUE SENSOR

Address to:

Assistant Commissioner for Patents
Washington, D.C. 20231**37 CFR 1.97(b)**

1. ☐ The Information Disclosure Statement submitted herewith is being filed within three months of the filing of a national application other than a continued prosecution application under 37 CFR 1.53(d); within three months of the date of entry of the national stage as set forth in 37 CFR 1.491 in an international application; before the mailing of a first Office Action on the merits, or before the mailing of a first Office Action after the filing of a request for continued examination under 37 CFR 1.114.

37 CFR 1.97(c)

2. ☒ The Information Disclosure Statement submitted herewith is being filed after the period specified in 37 CFR 1.97(b), provided that the Information Disclosure Statement is filed before the mailing date of a Final Action under 37 CFR 1.113, a Notice of Allowance under 37 CFR 1.311, or an Action that otherwise closes prosecution in the application, and is accompanied by one of:
- ☐ the statement specified in 37 CFR 1.97(e);
- OR**
- ☒ the fee set forth in 37 CFR 1.17(p).

01/22/2002 DTESSEN1 00000091 09663030

01 Fee:126


180.00 DP

TRANSMITTAL OF INFORMATION DISCLOSURE STATEMENT

(Under 37 CFR 1.97(b) or 1.97(c))

Docket No.
DE3-0089/DP-300793

In Re Application: THADDEUS SCHRODER ET AL



Serial No.

09/663,030

Filing Date

September 15, 2000

Examiner

D. DePumpo

Group Art Unit

3611

PIEZORESISTIVE TORQUE SENSOR

RECEIVED

JAN 24 2002

GROUP 3600**Payment of Fee**

(Only complete if Applicant elects to pay the fee set forth in 37 CFR 1.17(p))

- ☒ A check in the amount of \$180.00 is attached.
- ☒ The Assistant Commissioner is hereby authorized to charge and credit Deposit Account No. 06-1130 as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of
- ☒ Credit any overpayment.
- ☒ Charge any additional fee required.

Certificate of Transmission by Facsimile*

I certify that this document and authorization to charge deposit account is being facsimile transmitted to the United States Patent and Trademark Office (F

(Date)

Signature

Typed or Printed Name of Person Signing Certificate

Certificate of Mailing by First Class Mail

I certify that this document and fee is being deposited on October 26, 2001 with the U.S. Postal Service as first class mail under 37 C.F.R. 1.8 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Mary E. Arnold

Typed or Printed Name of Person Mailing Certificate

*This certificate may only be used if paying by deposit account.

George J. Lyman

Registration No. 44,884

Customer No. 23413

Dated:

CC:

3611

CERTIFICATE OF MAILING BY FIRST CLASS MAIL (37 CFR 1.8)

Applicant(s): SCHROEDER ET AL

Docket No.

DE3-0089

Serial No.

09/663,030

Filing Date

September 15, 2000


Examiner

DePumpo

Group Art Unit

3611

Invention: PIEZORESISTIVE TORQUE SENSOR



RECEIVED

JAN 24 2002

GROUP 3600

I hereby certify that this Information Disclosure Statement, Form PTO 1449 with copy of (1) cited reference
(Identify type of correspondence)

is being deposited with the United States Postal Service as first class mail in an envelope addressed to: The



Assistant Commissioner for Patents, Washington, D.C. 20231 on October 26, 2001
(Date)

Mary E. Arnold


(Typed or Printed Name of Person Mailing Correspondence)

(Signature of Person Mailing Correspondence)

Note: Each paper must have its own certificate of mailing.



(a)



(b)

FIGURE 23.6 Beam-type load cells: (a) a selection of beam-type load cells (elastic element with strain gages) and (b) gage positions in the Wheatstone bridge [3].

Beam-Type Load Cell

Beam-type load cells are commonly employed for measuring low-level loads [3]. A simple cantilever beam (see Figure 23.6(a)) with four strain gages, two on the top surface and two on the bottom surface (all oriented along the axis of the beam) is used as the elastic member (sensor) for the load cell. The gages are wired into a Wheatstone bridge as shown in Figure 23.6(b). The load P produces a moment $M = Px$ at the gage location (x) that results in the following strains:

$$\epsilon_1 = -\epsilon_2 = \epsilon_3 = -\epsilon_4 = \frac{6M}{Ebh^2} = \frac{6Px}{Ebh^2} \quad (23.9)$$

where b is the width of the cross-section of the beam and h is the height of the cross-section of the beam. Thus, the response of the strain gages is obtained from Equation 23.10.

$$\frac{\Delta R_1}{R_1} = -\frac{\Delta R_2}{R_2} = \frac{\Delta R_3}{R_3} = -\frac{\Delta R_4}{R_4} = \frac{6S_g Px}{Ebh^2} \quad (23.10)$$

The output voltage E_o from the Wheatstone bridge, resulting from application of the load P , is obtained from Equation 23.11. If the four strain gages on the beam are assumed to be identical, then Equation 23.11 holds.

$$E_o = \frac{6S_g Px E_1}{Ebh^2} \quad (23.11)$$

The range and sensitivity of a beam-type load cell depends on the shape of the cross-section of the beam, the location of the point of application of the load, and the fatigue strength of the material from which the beam is fabricated.

Ring-Type Load Cell

Ring-type load cells incorporate a proving ring (see Figure 23.7) as the elastic element. The ring element can be designed to cover a very wide range of loads by varying the diameter D , the thickness t , or the depth w of the ring. Either strain gages or a linear variable-differential transformer (LVDT) can be used as the sensor.

The load P is linearly proportional to the output voltage E_o . The sensitivity of the ring-type load cell with an LVDT sensor depends on the geometry of the ring (R , t , and w), the material from which the ring is fabricated (E), and the characteristics of the LVDT (S and E_1). The range of a ring-type load cell is controlled by the strength of the material used in fabricating the ring.